FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO LyondellBasell Acetyls, LLC

AUTHORIZING THE OPERATION OF LyondellBasell Syngas Industrial Gas Manufacturing

LOCATED AT

Harris County, Texas Latitude 29° 42′ 18″ Longitude 95° 3′ 20″ Regulated Entity Number: RN100217207

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No:	O2290	Issuance Date:	June 7, 2017	
For the Co	mmission			

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions:	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting	1
Additional Monitoring Requirements	
New Source Review Authorization Requirements	
Compliance Requirements	10
Protection of Stratospheric Ozone	
Permit Location	
Permit Shield (30 TAC § 122.148)	12
Attachments	13
Applicable Requirements Summary	14
Additional Monitoring Requirements	62
Permit Shield	
New Source Review Authorization References	70
Appendix A	75
Acronym List	76

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

- 1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subparts F, G, H, ZZZZ, and DDDDD as identified in the attached Applicable Requirements Summary table are subject to 30 TAC

- Chapter 113, Subchapter C, §113.110, 113.120, 113.130, 113.1090, and 113.1130 respectively, which incorporate the 40 CFR Part 63 Subpart by reference.
- F. For the purpose of generating emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 1 (Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 101.302 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.303 (relating to Emission Reduction Credit Generation Certification)
 - (iii) Title 30 TAC § 101.304 (relating to Mobile Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.309 (relating to Emission Credit Banking and Trading)
 - (v) The terms and conditions by which the emission limits are established to generate the reduction credit are applicable requirements of this permit
- G. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:
 - (i) Title 30 TAC § 101.352 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)
 - (iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)
 - (iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.359 (relating to Reporting)
 - (vi) Title 30 TAC § 101.360 (relating to Level of Activity Certification)
 - (vii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- For the purpose of generating discrete emission reduction credits through
 30 TAC Chapter 101, Subchapter H, Division 4 (Discrete Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 101.372 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.373 (relating to Discrete Emission Reduction Credit Generation and Certification)
 - (iii) Title 30 TAC § 101.374 (relating to Mobile Discrete Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.378 (relating to Discrete Emission Credit Banking and Trading)
 - (v) The terms and conditions by which the emission limits are established to generate the discrete reduction credit are applicable requirements of this permit

- I. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:
 - (i) Title 30 TAC § 101.393 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.394 (relating to Allocation of Allowances)
 - (iii) Title 30 TAC § 101.396 (relating to Allowance Deductions)
 - (iv) Title 30 TAC § 101.399 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.400 (relating to Reporting)
 - (vi) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- 2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
- 3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
 - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)

- (ii) Title 30 TAC § 111.111(a)(1)(E)
- (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
- (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:
 - (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
 - (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
 - (3) Records of all observations shall be maintained.
 - (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
 - (5) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
- However, if visible emissions are present during the observation, (b) the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.
- B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
 - (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed

facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A).
- However, if visible emissions are present during the observation. (b) the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- C. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- D. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by [h_e/H_e]² as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)

- E. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
 - (i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)
 - (ii) Title 30 TAC § 111.207 (relating to Exception for Recreation, Ceremony, Cooking, and Warmth)
 - (iii) Title 30 TAC § 111.219 (relating to General Requirements for Allowable Outdoor Burning)
 - (iv) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)
- 4. For industrial wastewater specified in 30 TAC Chapter 115, Subchapter B, the permit holder shall comply with the following requirements for wastewater drains, junction boxes, lift stations and weirs:
 - A. Title 30 TAC § 115.142 (relating to Control Requirements)
 - B. Title 30 TAC § 115.142(1)(A) (D) (relating to Control Requirements)
 - C. Title 30 TAC § 115.142(1)(E) and (F) (relating to Control Requirements)
 - D. Title 30 TAC § 115.142(1)(G) and (H) (relating to Control Requirements)
 - E. Title 30 TAC § 115.144(1), (5), and (6) (relating to Inspection and Monitoring Requirements)
 - F. Title 30 TAC § 115.145 (relating to Approved Test Methods)
 - G. Title 30 TAC § 115.146 (relating to Recordkeeping Requirements)
 - H. Title 30 TAC § 115.148 (relating to Determination of Wastewater Characteristics)
- 5. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(3)(A) for vent streams having no potential to emit HRVOC.
- 6. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(3)(A) for vent streams from sources exempt under 30 TAC § 115.727(c)(3).
- 7. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)

- F. Title 40 CFR § 60.14 (relating to Modification)
- G. Title 40 CFR § 60.15 (relating to Reconstruction)
- H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
- 8. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
- 9. For the chemical manufacturing process specified in 40 CFR Part 63, Subpart F, the permit holder shall comply with 40 CFR § 63.103(a) (relating to General Compliance, Reporting, and Recordkeeping Provisions) (Title 30 TAC Chapter 113, Subchapter C, § 113.110 incorporated by reference).
- 10. For the chemical manufacturing facilities with a 40 CFR Part 63, Subpart G Group 2 wastewater stream, the permit holder shall comply with (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
 - A. Title 40 CFR § 63.132(a), (a)(1), and (a)(1)(i) (relating to Process Wastewater Provisions General)
 - B. Title 40 CFR § 63.146(b)(1) (relating to Process Wastewater Provisions Reporting)
 - C. Title 40 CFR § 63.147(b)(8) (relating to Process Wastewater Provisions Recordkeeping)
- 11. For the transfer of Group 1 wastewater streams or residuals from Group 1 wastewater streams the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 63.132(g) (relating to Process Wastewater Provisions General)
 - B. Title 40 CFR § 63.152(b)(5) and (c)(4)(iv) (relating to General Reporting and Continuous Records)
- 12. For the chemical manufacturing facilities subject to leak detection requirements in 40 CFR Part 63, Subpart G, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
 - A. General Leak Detection Requirements:
 - (i) Title 40 CFR § 63.148(d)(1) (3), and (e) (relating to Leak Inspection Provisions)
 - (ii) Title 40 CFR § 63.148(c), (g), (g)(2), (h), and (h)(2) (relating to Leak Inspection Provisions), for monitoring and testing requirements
 - (iii) Title 40 CFR §§ 63.148(g)(2), (h)(2), (i)(1) (2), (i)(4)(i) (viii), (i)(5), and 63.152(a)(1) (5), for recordkeeping requirements
 - (iv) Title 40 CFR §§ 63.148(j), 63.151(a)(6)(i) (iii), (b)(1) (2), (j)(1) (3), 63.152(a)(1) (5), (b), (b)(1)(i) (ii), and (b)(4), for reporting requirements
 - B. For closed vent system or vapor collection systems constructed of hard piping:
 - (i) Title 40 CFR § 63.148(b)(1)(ii) (relating to Leak Inspection Provisions), for monitoring and testing requirements

- (ii) Title 40 CFR § 63.148(i)(6) (relating to Leak Inspection Provisions), for recordkeeping requirements
- C. For facilities not operating flow indicators:
 - (i) Title 40 CFR § 63.148(f)(2) (relating to Leak Inspection Provisions), for monitoring and testing requirements
 - (ii) Title 40 CFR § 63.148(i)(3)(ii) (relating to Leak Inspection Provisions), for recordkeeping requirements
 - (iii) Title 40 CFR § 63.148(j)(3) (relating to Leak Inspection Provisions), for reporting requirements
- 13. For the reloading or cleaning of railcars, tank trucks, and barges that deliver HAPs to a storage tank, the permit holder shall comply with the following requirements of 40 CFR § 63.119 (relating to Storage Vessel Provisions Reference Control Technology) (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
- 14. For the chemical manufacturing facilities subject to wastewater operations requirements in 40 CFR Part 63, Subpart G, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
 - A. Title 40 CFR § 63.136(a) (relating to Process Wastewater Provisions Individual Drain Systems)
 - B. Title 40 CFR § 63.136(b) (d) (relating to Process Wastewater Provisions Individual Drain Systems)
 - C. Title 40 CFR § 63.136(e) (g) (relating to Process Wastewater Provisions Individual Drain Systems)
- 15. For the chemical manufacturing facilities subject to requirements of certain liquid streams in 40 CFR Part 63, Subpart G, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
 - A. Title 40 CFR § 63.149(a), for control requirements
 - B. Title 40 CFR § 63.152(a)(1) (5) (relating to General Reporting and Continuous Records)
 - C. Title 40 CFR §§ 63.151(a)(6)(i) (v), (b)(1) (2), (j)(1) (3), 63.152(a)(1) (5), (b), (b)(1)(i) (ii), (b)(4) (relating to Initial Notification)

Additional Monitoring Requirements

16. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular

instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

- 17. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
- 18. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
- 19. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

- 20. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
- 21. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
 - A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
 - (i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:
 - (1) Title 30 TAC § 117.9020(2)(A), (C), and (D)

- B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.350(c) and (c)(1).
- C. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.
- 22. Use of Emission Credits to comply with applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)
 - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
 - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
- 23. Use of Discrete Emission Credits to comply with the applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables
 - B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)

- (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101. Subchapter H. Division 4
- (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
- (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Protection of Stratospheric Ozone

- 24. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
 - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Permit Location

25. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

26. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Unit Summary	. 15
Applicable Requirements Summary	. 22

Note: A "none" entry may be noted for some emission sources in this permit's "Applicable Requirements Summary" under the heading of "Monitoring and Testing Requirements" and/or "Recordkeeping Requirements" and/or "Reporting Requirements." Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
38-3-5A	STORAGE TANKS/VESSELS	N/A	R115-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
38-3-5B	STORAGE TANKS/VESSELS	N/A	R115-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
DEGREASER	SOLVENT DEGREASING MACHINES	N/A	R115	30 TAC Chapter 115, Degreasing Processes	No changing attributes.
DGRP1WW			63-G	40 CFR Part 63, Subpart G	No changing attributes.
GRP1WW	RP1WW TREATMENT PROCESS		63-G1	40 CFR Part 63, Subpart G	Control Device Type = Approved control device other than those specified in Subpart G.
GRP1WW TREATMENT PROCESS		WW-103-34-10, WW-103-34-8, WW- 103-34-9, WW-103- 35-11	63-G2	40 CFR Part 63, Subpart G	Control Device Type = Flare., Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested., Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.
POXNH3FLARE	ARE FLARES N/A		R111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
PW310-50-1	SRIC ENGINES	ENGINES N/A		30 TAC Chapter 117, Subchapter B	No changing attributes.
PW310-50-1	SRIC ENGINES	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
ROCGEN	SRIC ENGINES	N/A	60JJJJ-1	40 CFR Part 60, Subpart JJJJ	No changing attributes.
ROCGEN	SRIC ENGINES	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
SG13-20-1	STORAGE TANKS/VESSELS	N/A	R115-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG13-20-1	STORAGE TANKS/VESSELS	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
SG13-25-1	STORAGE TANKS/VESSELS	N/A	R115-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG13-25-1	STORAGE TANKS/VESSELS	N/A	63G-2	40 CFR Part 63, Subpart G	No changing attributes.
SG13-6-10	STORAGE TANKS/VESSELS	N/A	R115-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG20-2-2	FLARES	N/A	R111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
SG20-2-2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R115	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
SG20-2-2	FLARES	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.
SG20-3-2	FLARES	N/A	R111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
SG20-3-2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
SG20-3-2	FLARES	N/A	R5720-01	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
SG20-3-2	FLARES	N/A	60A-1	40 CFR Part 60, Subpart A	Flare Assist Type = Non-assisted,

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec), Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4)(i)-(iii) or (c)(5).
SG20-3-2	FLARES	N/A	60A-2	40 CFR Part 60, Subpart A	Adhering to Heat Content Specifications = Adhering to the requirements in 40 CFR § 60.18(c)(3)(i).
SG20-3-2	FLARES	N/A	63A-1	40 CFR Part 63, Subpart A	Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8)., Flare Assist Type = Non-assisted, Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)
SG20-3-2	FLARES	N/A	63A-2	40 CFR Part 63, Subpart A	Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(i).
SG2022VENT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R115-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
SG2022VENT	EMISSION POINTS/STATIONARY	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.

Unit/Group/ Process ID No.			SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				
SG2032VENT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R115-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
SG2032VENT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
SG21-1-1	FLARES	N/A	R111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
SG21-1-1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
SG21-1-1	FLARES	N/A	R5720-01	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
SG21-1-1 FLARES		N/A	60A-1	40 CFR Part 60, Subpart A	Flare Assist Type = Non-assisted, Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec), Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4)(i)-(iii) or (c)(5).
SG21-1-1	FLARES N/A 60A-2 40 CFR Part 60, Subpa		40 CFR Part 60, Subpart A	Adhering to Heat Content Specifications = Adhering to the requirements in 40 CFR § 60.18(c)(3)(i).	
SG21-1-1	FLARES	N/A	63A-1	40 CFR Part 63, Subpart A	Heat Content Specification = Adhering to the heat content specifications in 40 CFR §

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8)., Flare Assist Type = Non-assisted, Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)
SG21-1-1	FLARES	N/A	63A-2	40 CFR Part 63, Subpart A	Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(i).
SG21-6-1	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG2111VENT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R115-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
SG2111VENT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63G-1	40 CFR Part 63, Subpart G	No changing attributes.
SG23-50-1	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R117-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
SG23-50-1	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-1	40 CFR Part 60, Subpart Db	No changing attributes.
SG23-50-1	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
SG23-51-1	PROCESS HEATERS/FURNACES	N/A	R117	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
SG23-51-1	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60DB-1	40 CFR Part 60, Subpart Db	No changing attributes.
SG23-51-1	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
SG41-31-1	LOADING/UNLOADING OPERATIONS	N/A	R115	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
SG41-31-1	LOADING/UNLOADING OPERATIONS	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
SG5-1-1	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG5-1-11	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG5-1-14	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG5-1-17	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG5-7-1	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG7-7-11	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG810-21-1	10-21-1 STORAGE TANKS/VESSELS		R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG810-22-1	0-22-1 STORAGE N/A TANKS/VESSELS		R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG810-27-1 STORAGE TANKS/VESSELS		N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
SG811-1-1	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SG811-3-1	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
SGCT	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R115	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
SGCT	CHEMICAL MANUFACTURING PROCESS	N/A	63F	40 CFR Part 63, Subpart F	No changing attributes.
SGFUG	FUGITIVE EMISSION UNITS	N/A	R115	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
SGFUG	FUG FUGITIVE EMISSION UNITS		63H	40 CFR Part 63, Subpart H	No changing attributes.
WW-105-20-1	TREATMENT PROCESS N/A		63-G	40 CFR Part 63, Subpart G	No changing attributes.
WW-5-8-1	TREATMENT PROCESS	N/A	63-G	40 CFR Part 63, Subpart G	No changing attributes.

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
38-3-5A	EU	R115-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
38-3-5B	EU	R115-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
DEGREASE R	EU	R115	voc	30 TAC Chapter 115, Degreasing Processes	§ 115.412(1) § 115.411(1) [G]§ 115.412(1)(A) § 115.412(1)(C) § 115.412(1)(D) § 115.412(1)(E) [G]§ 115.412(1)(F)	Cold solvent cleaning. No person shall own or operate a system utilizing a VOC for the cold solvent cleaning of objects without the controls listed in §115.412(1)(A)-(F).	[G]§ 115.415(1) § 115.415(3) ** See Periodic Monitoring Summary	None	None
DGRP1WW	PRO	63-G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.138(h) [G]§ 63.132(f) § 63.138(h)(1) § 63.138(h)(2)(ii) § 63.138(h)(2)(iii) § 63.138(h)(3) [G]§ 63.138(k) § 63.140(a) § 63.140(b) § 63.144(a)	Treatment units in a RCRA unit option shall meet §63.138(h)(1), (h)(2), or (h)(3), and are exempt from §63.138(a)(3), §63.138(j), §63.132(a)(2)(iii) and §63.132(b)(3)(iii)	None	§ 63.147(b) § 63.147(b)(7) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(4) § 63.146(b)(5) § 63.146(b)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GRP1WW	PRO	63-G1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.138(e)(2) [G]§ 63.132(f) § 63.138(a)(7)(i)(A) [G]§ 63.138(k) § 63.139(b) § 63.139(c)(5)	Reduce mass flow rate of Table 8 and/or Table 9 compounds in Group 1 wastewater stream as specified. The	§ 63.138(a)(7)(i)(D) § 63.138(j)(2) § 63.139(e) § 63.143(d) § 63.143(e) § 63.143(e)(3)	§ 63.138(a)(7)(i)(C) § 63.143(e)(3) § 63.144(b)(3) § 63.144(b)(4) § 63.144(b)(5)(ii) § 63.144(c)(1)	§ 63.138(a)(7)(i)(C) § 63.143(d) § 63.143(e)(3) § 63.146(a) § 63.146(b)(2) § 63.146(b)(4)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) § 63.145(c)(6) § 63.172(a) [G]§ 63.172(h) § 63.172(j)	process efficiency shall be computed as per §63.145(c) or §63.145(d).	\$ 63.143(g) \$ 63.144(b) \$ 63.144(b)(2) \$ 63.144(b)(3) \$ 63.144(b)(5) [G]\$ 63.144(b)(5)(ii) [G]\$ 63.144(b)(5)(iii) § 63.144(b)(5)(iii) § 63.144(b)(5)(iii) § 63.144(b)(5)(iii) § 63.144(b)(6) § 63.144(c)(1) § 63.144(c)(2) § 63.144(c)(2) § 63.144(c)(3) § 63.145(a)(1) § 63.145(a)(5) [G]\$ 63.145(a)(6) § 63.145(c)(1) § 63.145(c)(1) § 63.145(c)(2) § 63.145(c)(2) § 63.145(c)(3) § 63.145(c)(4) § 63.145(c)(5) § 63.145(c)(6) [G]\$ 63.172(f)(1) [G]\$ 63.172(f)(2) § 63.172(g) [G]\$ 63.172(h) [G]\$ 63.172(h) [G]\$ 63.172(l) [G]\$ 63.172(l) [G]\$ 63.172(l) [G]\$ 63.172(l) [G]\$ 63.172(l) [G]\$ 63.172(l) [G]\$ 63.172(l) [G]\$ 63.172(l) [G]\$ 63.172(l) [G]\$ 63.172(l)	§ 63.144(c)(2) § 63.144(c)(3) § 63.147(b) § 63.147(b)(5) § 63.147(b)(7) § 63.147(e) [G]§ 63.152(a) [G]§ 63.152(t) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(ii) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	§ 63.146(b)(5) § 63.146(b)(6) [G]§ 63.146(b)(9) § 63.146(b)(9)(ii) [G]§ 63.146(d) § 63.151(e) [G]§ 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) § 63.151(e)(5) § 63.151(f)(1) § 63.151(f)(1) § 63.151(f)(1) § 63.151(f)(2) § 63.151(f)(2) § 63.151(f)(2) § 63.151(f)(3) § 63.151(f)(2) § 63.151(f)(3) § 63.151(f)(2) § 63.151(f)(2) § 63.151(f)(3) § 63.151(f)(2) § 63.151(f)(3) § 63.152(e) [G]§ 63.152(e) § 63.152(e) § 63.152(e) § 63.152(e)(1) § 63.152(c)(1) § 63.152(c)(3) § 63.152(c)(3) § 63.152(c)(3)(ii) § 63.152(c)(4)(iii) [G]§ 63.182(e) [G]§ 63.182(e) § 63.182(c) [G]§ 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(c)(4) [G]§ 63.182(c)(4) [G]§ 63.182(c)(4) [G]§ 63.182(c)(4)
GRP1WW	PRO	63-G2	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.138(e)(2) § 63.11 [G]§ 63.132(f)	Reduce mass flow rate of Table 8 and/or Table 9	§ 63.138(j)(2) § 63.139(d)(3) § 63.139(e)	§ 63.144(b)(3) § 63.144(b)(4) § 63.144(b)(5)(ii)	§ 63.143(d) § 63.146(a) § 63.146(b)(2)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.138(a)(7)(i)(A) [G]§ 63.138(k) § 63.139(b) § 63.139(c)(3) § 63.139(f) § 63.140(a) § 63.140(c) § 63.144(a) § 63.145(c)(6) [G]§ 63.145(j) § 63.172(a) [G]§ 63.172(h) § 63.172(i)	compounds in Group 1 wastewater stream as specified. The process efficiency shall be computed as per §63.145(c) or §63.145(d).	\$ 63.143(d) \$ 63.143(e) \$ 63.143(e) \$ 63.143(g) \$ 63.144(b) \$ 63.144(b)(1) \$ 63.144(b)(2) \$ 63.144(b)(5) [G]§ 63.144(b)(5) [G]§ 63.144(b)(5)(ii) \$ 63.144(b)(5)(iii) [G]§ 63.144(b)(5)(iii) \$ 63.144(b)(5)(iii) \$ 63.144(b)(6) \$ 63.144(c) \$ 63.144(c) \$ 63.144(c) \$ 63.144(c)(1) \$ 63.144(c)(2) \$ 63.144(c)(3) \$ 63.144(c)(3) \$ 63.145(a)(1) \$ 63.145(a)(3) [G]§ 63.145(a)(5) [G]§ 63.145(a)(6) \$ 63.145(c)(1) \$ 63.172(f)(1) [G]§ 63.172(f)(1) [G]§ 63.172(h) [G]§ 63.172(h) [G]§ 63.172(l) [G]§ 63.172(l)	§ 63.144(c)(1) § 63.144(c)(2) § 63.144(c)(3) § 63.145(a)(3) [G]§ 63.145(a)(4) § 63.147(b) § 63.147(b)(5) § 63.147(b)(7) § 63.147(d)(1) § 63.147(d)(1) § 63.147(e) [G]§ 63.152(a) [G]§ 63.152(f) [G]§ 63.172(k) [G]§ 63.172(k) [G]§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(ii) § 63.181(g)(1)(ii) § 63.181(g)(2) [G]§ 63.181(g)(3)	\$ 63.146(b)(4) \$ 63.146(b)(5) \$ 63.146(b)(6) \$ 63.146(b)(7) [G]\$ 63.146(b)(9) \$ 63.146(b)(9)(ii) [G]\$ 63.146(b)(9)(iii) [G]\$ 63.146(d) \$ 63.146(e) \$ 63.146(e) \$ 63.146(f) [G]\$ 63.151(e) [G]\$ 63.151(e) [G]\$ 63.151(e)(1) \$ 63.151(e)(2) \$ 63.151(e)(3) \$ 63.151(e)(5) \$ 63.151(f)(3) \$ 63.151(f)(2) \$ 63.152(b) [G]\$ 63.152(b) [G]\$ 63.152(b) [G]\$ 63.152(b) [G]\$ 63.152(c)(1) \$ 63.152(c)(3)(ii) \$ 63.152(c)(4)(iii) [G]\$ 63.152(c)(6) [G]\$ 63.182(a) [G]\$ 63.182(a) [G]\$ 63.182(b) \$ 63.182(c) [G]\$ 63.182(c) [G]\$ 63.182(c) [G]\$ 63.182(c) [G]\$ 63.182(c) [G]\$ 63.182(c) [G]\$ 63.182(c)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.180(d)		[G]§ 63.182(d)
POXNH3FL ARE	EU	R111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
PW310-50-1	EU	R117	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
PW310-50-1	EU	63ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6603(a)- Table2d.4	For each existing emergency	§ 63.6625(f) § 63.6625(i)	§ 63.6625(i) § 63.6655(a)	§ 63.6640(b) § 63.6640(e)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.6595(a)(1) § 63.6604(b) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) [G]§ 63.6640(f)(4)	stationary CI RICE and black start stationary CI RICE, located at an area source, you must comply with the requirements as specified in Table 2d.4.a-c.	§ 63.6640(a) § 63.6640(a)- Table6.9.a.i § 63.6640(a)- Table6.9.a.ii § 63.6640(b)	§ 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6650(a)-Table7.4 § 63.6650(f) [G]§ 63.6650(h)
ROCGEN	EU	60JJJJ-1	S	40 CFR Part 60, Subpart JJJJ	§ 60.4233(d)-Table1 § 60.4234 § 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g) § 60.4246	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than 25 HP and less than 130 HP and were manufactured on or after 01/01/2009 must comply with a CO emission limit of 387 g/HP-hr, as listed in Table 1 to this subpart.	§ 60.4237(c)	§ 60.4243(a)(1) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b)	None
ROCGEN	EU	60JJJJ-1	HC and NO _X	40 CFR Part 60, Subpart JJJJ	§ 60.4233(d)-Table1 § 60.4234 § 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g) § 60.4246	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than 25 HP and less than 130 HP and were manufactured on or after 01/01/2009	§ 60.4237(c)	§ 60.4243(a)(1) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						must comply with an HC+NOx emission limit of 10 g/HP-hr, as listed in Table 1 to this subpart.			
ROCGEN	EU	63ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
SG13-20-1	EU	R115-1	voc	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
SG13-20-1	EU	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.11 § 63.119(a)(1) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) [G]§ 63.148(d) § 63.148(e)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with§63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(e)(1) § 63.120(e)(4) § 63.120(e)(5) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.123(a) [G]§ 63.123(f)(2) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a)	[G]§ 63.120(e)(2) § 63.122(c)(2) [G]§ 63.122(g)(1) [G]§ 63.122(g)(3) § 63.148(j) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(ii) [G]§ 63.152(c)(2)(iii) § 63.152(c)(2)(iii) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) § 63.152(c)(4)(ii) § 63.152(c)(4)(ii) § 63.152(c)(4)(ii)
SG13-25-1	EU	R115-2	VOC	30 TAC Chapter 115, Storage of	§ 115.112(e)(1) § 115.112(e)(2)	No person shall place, store, or hold	§ 115.114(a)(1) § 115.114(a)(1)(A)	§ 115.118(a)(3) § 115.118(a)(5)	§ 115.114(a)(1)(B)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	§ 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117	§ 115.118(a)(6)(C) § 115.118(a)(7)	
SG13-25-1	EU	63G-2	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(5)(viii) § 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(iii) § 63.122(d)(2)(iii) § 63.122(d)(2)(iii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(iii)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SG13-6-10	EU	R115-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
SG20-2-2	EU	R111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
SG20-2-2	EP	R115	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(B) § 60.18	Vent gas streams affected by §115.121(a)(1) must be controlled properly with a	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices).			
SG20-2-2	CD	63A	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
SG20-3-2	EU	R111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
SG20-3-2	EP	R5720	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.			
SG20-3-2	EP	R5720-01	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(e)(1) § 115.725(e)(2) § 115.725(e)(3) § 115.725(f)(1) § 115.725(f)(2) § 115.725(f)(3) § 115.725(f)(5) § 115.725(g)(2)(B)(i) [G]§ 115.725(g)(2)(C) § 115.725(g)(2)(D) [G]§ 115.725(l)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(e)(1) § 115.725(e)(2) § 115.725(e)(3) § 115.725(f)(1) § 115.725(f)(2) § 115.725(f)(3) § 115.725(f)(4)(A) § 115.725(g)(2)(B)(i) § 115.725(g)(2)(B)(ii) § 115.725(g)(2)(B)(ii) [G]§ 115.725(g)(2)(C) § 115.725(g)(2)(D) § 115.725(g)(2)(D) § 115.725(k)(2) [G]§ 115.725(l) § 115.725(n)	§ 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) [G]§ 115.726(d)(5) § 115.726(d)(7) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n)
SG20-3-2	CD	60A-1	Opacity	40 CFR Part 60,	§ 60.18(b)	Flares shall comply	§ 60.18(d)	None	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart A	§ 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	with paragraphs (c)- (f) of § 60.18.	§ 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)		
SG20-3-2	CD	60A-2	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(i)(A) § 60.18(c)(3)(i)(B) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(4)	None	None
SG20-3-2	CD	63A-1	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
SG20-3-2	CD	63A-2	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(i)(A) § 63.11(b)(6)(i)(B) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SG2022VEN T	EP	R115-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(2) § 115.121(a)(2) § 115.122(a)(2)(A) § 60.18	Any vent gas streams affected by §115.121(a)(2) of this title must be controlled properly with a control efficiency of at least 98% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
SG2022VEN T	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare.§63.113(a)(1)(i) -(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	[G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2) § 63.152(c)(2)(iii) § 63.152(c)(2)(iiii) § 63.152(c)(2)(iiii) § 63.152(c)(4)(iii) [G]§ 63.152(c)(4)(iii) [G]§ 63.152(c)(6)
SG2032VEN T	EP	R115-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(2) § 115.121(a)(2) § 115.122(a)(2)(A)	Any vent gas streams affected by §115.121(a)(2) of	[G]§ 115.125 § 115.126(1) § 115.126(1)(B)	§ 115.126 § 115.126(1) § 115.126(1)(B)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.18	this title must be controlled properly with a control efficiency of at least 98% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	§ 115.126(2) § 115.126(7)	§ 115.126(2)	
SG2032VEN T	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare.§63.113(a)(1)(i) -(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	[G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2) § 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iii) § 63.152(c)(4)(iii) [G]§ 63.152(c)(4)(iii) [G]§ 63.152(c)(6)
SG21-1-1	EU	R111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period.	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Non-excessive upset events are subject to the provisions under §101.222(b).			
SG21-1-1	EP	R5720	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None
SG21-1-1	EP	R5720-01	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(e)(1) § 115.725(e)(2) § 115.725(e)(3) § 115.725(f)(1)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when	[G]§ 115.725(d)(1) § 115.725(e)(1) § 115.725(e)(2) § 115.725(e)(3) § 115.725(f)(1) § 115.725(f)(2) § 115.725(f)(3) § 115.725(f)(4)(A)	§ 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) [G]§ 115.726(d)(5) § 115.726(d)(7) § 115.726(i)	§ 115.725(n)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.725(f)(2) § 115.725(f)(3) § 115.725(f)(5) § 115.725(g)(2)(B)(i) [G]§ 115.725(g)(2)(C) § 115.725(g)(2)(D) [G]§ 115.725(l)	vent gas containing HRVOC is being routed to the flare.	§ 115.725(f)(5) § 115.725(g)(2)(B)(i) § 115.725(g)(2)(B)(ii) [G]§ 115.725(g)(2)(C) § 115.725(g)(2)(D) § 115.725(k)(2) [G]§ 115.725(l) § 115.725(n)	§ 115.726(j)(1) § 115.726(j)(2)	
SG21-1-1	CD	60A-1	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
SG21-1-1	CD	60A-2	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(i)(A) § 60.18(c)(3)(i)(B) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(4)	None	None
SG21-1-1	CD	63A-1	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
SG21-1-1	CD	63A-2	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2)	Flares shall be designed and operated with no	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(i)(A) § 63.11(b)(6)(i)(B) § 63.11(b)(7)(i)	visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.			
SG21-6-1	EU	R115	voc	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
SG2111VEN T	EP	R115-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(2) § 115.121(a)(2) § 115.122(a)(2)(A) § 60.18	Any vent gas streams affected by §115.121(a)(2) of this title must be controlled properly with a control efficiency of at least 98% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
SG2111VEN T	EP	63G-1	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare.§63.113(a)(1)(i) -(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	[G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(ii) [G]§ 63.152(c)(2)(iii) § 63.152(c)(2)(iiii) § 63.152(c)(4)(iii) [G]§ 63.152(c)(6)
SG23-50-1	EU	R117-1	со	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(b) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f) § 117.335(f) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B) § 117.8100(a)(1)(C) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
SG23-50-1	EU	R117-1	NOx	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(1)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(3) § 117.340(e)(4) § 117.340(f)(1) § 117.340(f)(2) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(c)(1) [G]§ 117.340(f)(2) § 117.340(f)(2) § 117.340(f)(2) § 117.340(f)(2) § 117.340(f)(2) § 117.340(f)(2) § 117.340(f)(2) § 117.340(f)(1) § 117.340(f)(1) § 117.340(f)(2) § 117.340(f)(2) § 117.340(f)(2) § 117.340(f)(1) § 117.340(f)(1) § 117.340(f)(1) § 117.340(f)(1) § 117.340(f)(1) § 117.340(f)(1) § 117.340(f)(1) § 117.340(f)(f)(f) § 117.340(f)(f)(f) § 117.3400(f)(f)(f) § 117.3400(f)(f)(f) § 117.3400(f)(f)(f) § 117.3400(f)(f)(f) § 117.3400(f)(f)(f) § 117.3400(f)(f)(f) § 117.3400(f)(f)(f) § 117.3400(f)(f)(f)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8010(6)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
SG23-50-1	EU	60Db-1	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
SG23-50-1	EU	60Db-1	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
SG23-50-1	EU	60Db-1	SO ₂	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SG23-50-1	EU	63DDDDD -1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
SG23-51-1	EU	R117	СО	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(f) § 117.335(f) § 117.335(f) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B) § 117.8100(a)(1)(C) § 117.8100(a)(1)(C) § 117.8100(a)(1)(C) § 117.8100(a)(1)(C) § 117.8100(a)(1)(C) § 117.8100(a)(1)(C) § 117.8100(a)(1)(C) § 117.8100(a)(5) § 117.8100(a)(5) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(C) § 117.8100(a)(5)(C) § 117.8100(a)(5)(C) § 117.8100(a)(5)(C) [G]§ 117.8100(a)(5)(C) [G]§ 117.8100(a)(5)(C) [G]§ 117.8100(a)(5)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.345(g) [G]§ 117.345(b) [G]§ 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(7)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8120 § 117.8120(1) § 117.8120(1)(A)		
SG23-51-1	EU	R117	NOx	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(4) § 117.340(f)(1) § 117.340(f)(1) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(1) [G]§ 117.340(c)(1) [G]§ 117.340(c)(1) [G]§ 117.340(f)(2) § 117.340(f)(2) § 117.340(f)(2) § 117.340(g)(1) § 117.340(g)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B) § 117.8100(a)(1)(C) § 117.8100(a)(1)(C) § 117.8100(a)(1)(C) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5) § 117.8100(a)(5) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(5)(E)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(c) § 117.345(d) § 117.345(d) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
SG23-51-1	EU	60DB-1	NO _X	40 CFR Part 60, Subpart Db	§ 60.44b(e) § 60.44b(h) § 60.44b(i)	Except in §60.44b(l), on/after §60.8 tests, no facility firing	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(2)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.46b(a)	specified fuels shall discharge NOx in excess of the specified formula, unless subject to federal ACF of 10% or less.	[G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a)(3) § 60.49b(b) § 60.49b(i) § 60.49b(v) § 60.49b(w)
SG23-51-1	EU	60DB-1	РМ	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
SG23-51-1	EU	60DB-1	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
SG23-51-1	EU	60DB-1	SO ₂	40 CFR Part 60, Subpart Db	§ 60.42b(k)(2)	Units firing only very low sulfur oil and/or a mixture of gaseous fuels with a potential SO2 emission rate of 140 ng/J (0.32 lb/MMBtu) heat input	§ 60.47b(f)	§ 60.45b(k) § 60.49b(o) § 60.49b(r) § 60.49b(r)(1)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(r) § 60.49b(r)(1)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						or less are exempt from the SO2 emissions limit in §60.42b(k)(1).			
SG23-51-1	EU	63DDDDD -1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
SG41-31-1	EU	R115	voc	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(2)(A) § 115.212(a)(2) [G]§ 115.212(a)(7) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Any plant, excluding gasoline bulk plants, which loads less than 20,000 gpd of VOC with a true vapor pressure of 0.5 psia or greater is exempt from the requirements of this division, except for the specified requirements.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B) § 115.216(3)(D)	None
SG41-31-1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.126(c)	For each Group 2 transfer rack, maintain records as required in § 63.130(f). No other provisions for transfer racks apply to the Group 2 transfer rack.	None	§ 63.130(f) § 63.130(f)(1) § 63.130(f)(2) § 63.130(f)(3) § 63.130(f)(3)(i) § 63.130(f)(3)(ii)	§ 63.152(c)(4)(iii)
SG5-1-1	EU	R115	VOC	30 TAC Chapter 115, Storage of	§ 115.111(a)(1)	Except as provided in § 115.118, a	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs		storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(6)(A) § 115.118(a)(7)	
SG5-1-11	EU	R115	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
SG5-1-14	EU	R115	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
SG5-1-17	EU	R115	voc	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
SG5-7-1	EU	R115	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(7)	
SG7-7-11	EU	R115	voc	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
SG810-21-1	EU	R115	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
SG810-22-1	EU	R115	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
SG810-27-1	EU	R115	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						vapor pressure less than 1.5 psia is exempt from the requirements of this division.			
SG811-1-1	EU	R115	voc	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
SG811-3-1	EU	R115	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
SGCT	EU	R115	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.761(c)(1) § 115.761(c)(3) § 115.764(h)(1) [G]§ 115.764(h)(6) § 115.764(h)(8) § 115.766(i)	HRVOC emissions at each site located in Harris County that is subject to this division or Division 1 of this subchapter must not exceed 1,200 pounds of HRVOCs per one-hour block period from any flare, vent, pressure relief valve, cooling tower, or any combination.	§ 115.764(c) § 115.764(h)(1) § 115.764(h)(2) § 115.764(h)(3) § 115.764(h)(4) § 115.764(h)(5) § 115.764(h)(7)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(4) § 115.766(a)(5) § 115.766(a)(6) [G]§ 115.766(a)(7) § 115.766(c) [G]§ 115.766(g) [G]§ 115.766(h) § 115.766(i)(1)	§ 115.764(h)(8) § 115.766(i)(2)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SGCT	PRO	63F	112(B) HAPS	40 CFR Part 63, Subpart F	§ 63.100(b) [G]§ 63.102(a) [G]§ 63.102(c) § 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.105(d)	Except as provided in paragraphs (b)(4) and (c) of this section, the provisions of subparts F, G, and H apply to chemical manufacturing process units that meet the criteria.	§ 63.103(b)(1) § 63.103(b)(3) § 63.103(b)(4) [G]§ 63.103(b)(5) § 63.103(b)(6) [G]§ 63.104(b)	[G]§ 63.103(c) [G]§ 63.104(e)(2) [G]§ 63.104(f)(1) [G]§ 63.105(b) § 63.105(c) § 63.105(e)	§ 63.103(b)(2) [G]§ 63.103(b)(5) [G]§ 63.103(d) [G]§ 63.104(f)(2)
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(8)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(2)(C)(iiii) § 115.352(3) § 115.352(5)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(12) § 115.357(8)	methane, or the dripping or exuding of process fluid based on sight, smell, or sound.			
SGFUG	EU	R115	voc	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(2)(C)(iiii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
SGFUG	EU	R115	VOC	30 TAC Chapter	§ 115.352(1)(B)	No compressor seals	[G]§ 115.355	§ 115.352(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(2)(C)(iiii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355 § 115.357(1)	§ 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(12) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1) § 115.357(8) § 115.357(9)	methane, or the dripping or exuding of process fluid based on sight, smell, or sound.			
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight,	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						smell, or sound.			
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
SGFUG	EU	R115	voc	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10)	No process drains shall be allowed to have a VOC leak, for	§ 115.354(1) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
SGFUG	EU	R115	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.			
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c)	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171			[G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open- ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.172(d) § 63.11(b) § 63.172(e) [G]§ 63.172(h) § 63.172(m)	Flares used to comply with this subpart shall comply with the requirements of § 63.11(b) of 40 CFR 63, Subpart A.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)- (j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.172(a) [G]§ 63.172(h) § 63.172(i)	Owners/operators of closed-vent systems and control devices	[G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g)	§ 63.118(a)(3) § 63.172(j)(1) [G]§ 63.172(l)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.172(j)(1) § 63.172(j)(2) § 63.172(m)	used to comply with provisions of this subpart shall comply with the provisions of this section, except as provided in §63.162(b).	[G]§ 63.172(h) § 63.172(j)(1) § 63.172(j)(2) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
SGFUG	EU	63H	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
WW-105-20-	PRO	63-G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.138(h) [G]§ 63.132(f) § 63.138(h)(1) § 63.138(h)(2)(ii) § 63.138(h)(2)(ii) § 63.138(h)(3) [G]§ 63.138(k) § 63.140(a) § 63.140(b) § 63.144(a)	Treatment units in a RCRA unit option shall meet §63.138(h)(1), (h)(2), or (h)(3), and are exempt from §63.138(a)(3), §63.138(j), §63.132(a)(2)(iii) and §63.132(b)(3)(iii)	§ 63.144(b) § 63.144(b)(1) § 63.144(b)(2) § 63.144(b)(3) § 63.144(b)(5) [G]§ 63.144(b)(5)(ii) § 63.144(b)(5)(iii) [G]§ 63.144(b)(5)(iii) § 63.144(b)(5)(iv) § 63.144(c)(6) § 63.144(c)(1) § 63.144(c)(1) § 63.144(c)(2) § 63.144(c)(3) § 63.144(c)(4)	§ 63.144(b)(3) § 63.144(b)(4) § 63.144(b)(5)(ii) § 63.144(c)(1) § 63.144(c)(2) § 63.144(c)(3) § 63.147(b) § 63.147(b)(7) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(4) § 63.146(b)(5) § 63.146(b)(6) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(3) [G]§ 63.151(e)(3) [G]§ 63.151(b) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
WW-5-8-1	PRO	63-G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.138(h) [G]§ 63.132(f)	Treatment units in a RCRA unit option	None	§ 63.147(b) § 63.147(b)(7)	§ 63.146(b)(2) § 63.146(b)(4)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.138(h)(1) § 63.138(h)(2)(ii) § 63.138(h)(2)(ii) § 63.138(h)(3) [G]§ 63.138(k) § 63.140(a) § 63.140(b) § 63.144(a)	shall meet §63.138(h)(1), (h)(2), or (h)(3), and are exempt from §63.138(a)(3), §63.138(j), §63.132(a)(2)(iii) and §63.132(b)(3)(iiii)		[G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(5) § 63.146(b)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)

	Additional Monitoring Red	quirements	
Periodic Monitoring Summary			63

Periodic Monitoring Summary

Unit/Group/Process Information					
ID No.: DEGREASER					
Control Device ID No.: N/A	Control Device Type: N/A				
Applicable Regulatory Requirement					
Name: 30 TAC Chapter 115, Degreasing Processes	SOP Index No.: R115				
Pollutant: VOC	Main Standard: § 115.412(1)				
Monitoring Information					
Indicator: Visual Inspection					
Minimum Frequency: Monthly					
Averaging Period: N/A					
Deviation Limit: Any monitoring data indicating that the c requirements of 30 TAC Chapter 115, 115.412(1)(A) - (F)	•				

Periodic Monitoring Text: Inspect equipment and record data monthly to ensure compliance with any applicable requirements in § 115.412(1)(A)-(F). Any monitoring data which indicates that the cold cleaner is not in compliance with the applicable requirements of § 115.412(1)(A)-(F) shall be considered and reported as a deviation.

	Permit Shield	
Permit Shield		6

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
303-54-1	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
303-54-1	N/A	40 CFR Part 60, Subpart Kb	The vessel is not used for the storage of volatile organic liquids (VOL)
310-50-1.2	N/A	30 TAC Chapter 115, Storage of VOCs	The storage vessel has a capacity <1,000 gallons (3,785 L)
310-50-1.2	N/A	40 CFR Part 60, Subpart Kb	The vessel has a design capacity < 75 m3 (19,800 gal).
38-3-5A	N/A	40 CFR Part 60, Subpart Kb	The tank is not subject to Subpart Kb because it is a pressure vessel operating with a pressure rating > 29.7 psia (204.9 kPa) and without emissions to the atmosphere.
38-3-5A	N/A	40 CFR Part 63, Subpart G	Equipment capacity is less than 38 cubic meters and thus does not meet the definition of storage vessel per 63.101.
38-3-5B	N/A	40 CFR Part 60, Subpart Kb	The tank is not subject to Subpart Kb because it is a pressure vessel operating with a pressure rating > 29.7 psia (204.9 kPa) and without emissions to the atmosphere.
38-3-5B	N/A	40 CFR Part 63, Subpart G	Equipment capacity is less than 38 cubic meters and thus does not meet the definition of storage vessel per 63.101.
38-6-1	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile compounds (VOC)
38-6-1	N/A	40 CFR Part 60, Subpart Kb	The vessel is not used for the storage of volatile organic liquids (VOL)

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
7-2-3	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
7-2-3	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL
7-3-6	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
7-3-6	N/A	40 CFR Part 60, Subpart Kb	The vessel is not used for the storage of volatile organic liquids (VOL)
71-1-2	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
71-1-2	N/A	40 CFR Part 60, Subpart Kb	The vessel is not used for the storage of volatile organic liquids (VOL)
71-13-1	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
71-13-1	N/A	40 CFR Part 60, Subpart Kb	The vessel is not used for storage of volatile organic liquids (VOC)
71-13-2	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
71-13-2	N/A	40 CFR Part 60, Subpart Kb	Not storing a VOL
71-2-1	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
71-2-1	N/A	40 CFR Part 60, Subpart Kb	The vessel is not used for the storage of volatile organic liquids (VOL)
810-21-3	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
810-21-3	N/A	40 CFR Part 60, Subpart Kb	The vessel is not used for the storage of volatile

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			organic liquids (VOL)
810-28-8	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
810-28-8	N/A	40 CFR Part 60, Subpart Kb	The vessel is not used for the storage of volatile organic liquids (VOL)
810-29-6	N/A	30 TAC Chapter 115, Storage of VOCs	The vessel does not store volatile organic compounds (VOC)
810-29-6	N/A	40 CFR Part 60, Subpart Kb	The vessel is not used for the storage of volatile organic liquids (VOL)
POXNH3FLARE	N/A	30 TAC Chapter 115, HRVOC Vent Gas	The unit does not control any vent gas stream containing highly-reactive volatile organic compounds.
SG13-25-1	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids
SG13-25-1	N/A	40 CFR Part 63, Subpart EEEE	The unit is part of an affected source under another 40 CFR part 63 national emission standard for hazardous air pollutants. The unit is subject to the HON.
SG13-6-10	N/A	40 CFR Part 63, Subpart G	Unit is a surge control vessel and does not meet the definition of storage vessel contained in 63.101.
SG20-2-2	N/A	30 TAC Chapter 115, HRVOC Vent Gas	The unit does not control any vent gas stream containing highly-reactive volatile organic compounds.
SG21-6-1	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids
SG23-50-1	N/A	30 TAC Chapter 112, Sulfur Compounds	Does not burn solid or liquid fuel.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
SG23-50-1	N/A	40 CFR Part 60, Subpart Dc	Steam generating unit constructed, modified, or reconstructed after June 9, 1989 and has a maximum design heat input capacity greater than 100 MMBtu/hr.
SG23-51-1	N/A	30 TAC Chapter 112, Sulfur Compounds	Does not burn solid or liquid fuel.
SG31PSA1	N/A	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	Facility is not a synthetic organic chemical, polymer, resin, or methyl-tertiary-butylether manufacturing process, or natural gas/gasoline processing operation as defined in §115.10, or a petroleum refinery.
SG31PSA1	N/A	40 CFR Part 60, Subpart VV	The facility does not produce as an intermediate or final product one or more of the chemicals listed in 60.489.
SG31PSA1	N/A	40 CFR Part 60, Subpart VVa	Facility does not produce as an intermediate or final product one or more of the chemicals listed in 60.489a.
SG5-1-1	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids
SG5-1-11	N/A	40 CFR Part 60, Subpart Kb	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
SG5-1-14	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids
SG5-1-17	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids
SG5-7-1	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids.
SG810-21-1	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids
SG810-22-1	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
SG810-27-1	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids
SG811-1-1	N/A	40 CFR Part 60, Subpart Kb	Capacity is < 19,800 gallons.
SG811-3-1	N/A	40 CFR Part 60, Subpart Kb	Capacity is < 19,800 gallons.
SG930D	N/A	30 TAC Chapter 115, Storage of VOCs	The storage vessel has a capacity <1,000 gallons (3,785L)
SG930D	N/A	40 CFR Part 60, Subpart Kb	The vessel has a design capacity < 75 m3 (19,800 gal).
SG930U	N/A	30 TAC Chapter 115, Storage of VOCs	The storage vessel has a capacity <1,000 gallons (3,785L)
SG930U	N/A	40 CFR Part 60, Subpart Kb	The vessel has a design capacity < 75 m3 (19,800 gal).
SGCT	N/A	40 CFR Part 63, Subpart Q	Does not operate with chromium based water treatment chemicals.
SGFUG1C3C	N/A	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	Site does not contain a synthetic organic chemical manufacturing process, polymer, resin, or methyl-tertiary-butylether manufacturing process, natural gas/gasoline processing operation or a petroleum refinery as defined in §115.10.
SGFUG1C3C	N/A	40 CFR Part 60, Subpart VV	The facility does not produce as an intermediate or final product, one or more of the chemicals listed in 60.489.
SGFUG1C3C	N/A	40 CFR Part 60, Subpart VVa	The facility does not produce as an intermediate or final product one or more of the chemicals listed in 60.489a.
WASTEWATER	N/A	30 TAC Chapter 115, Industrial Wastewater	The facility is not an affected source category.

New Source Review Authorization References

New Source Review Authorization References	71
New Source Review Authorization References by Emission Unit	72

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 4773A	Issuance Date: 05/07/2013
Authorization No.: 40938	Issuance Date: 04/08/2021
Permits By Rule (30 TAC Chapter 106) for the	Application Area
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.372	Version No./Date: 09/04/2000
Number: 106.412	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 07/08/1998
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.492	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.532	Version No./Date: 09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
303-54-1	BULK LIME TANK	106.472/09/04/2000
310-50-1.2	DIESEL STORAGE TANK	4773A
38-3-5A	FEEDSTOCK TANK	4773A
38-3-5B	FEEDSTOCK TANK	4773A
38-6-1	PHOSPHATE STORAGE TANK	106.472/09/04/2000
7-2-3	FERROUS SULFATE TANK	106.472/09/04/2000
7-3-6	CAUSTIC DAY TANK	106.472/09/04/2000
71-1-2	BULK CAUSTIC STORAGE TANK	106.472/09/04/2000
71-13-1	FERROUS SULFATE TANK	106.472/09/04/2000
71-13-2	FERROUS SULFATE TANK	106.472/09/04/2000
71-2-1	BULK SULFURIC ACID TANK	106.472/09/04/2000
810-21-3	FERRIC SULFATE TANK	106.472/09/04/2000
810-28-8	PHOSPHORIC ACID DAY TANK	106.472/09/04/2000
810-29-6	PHOSPHORIC ACID TANK	106.472/09/04/2000
DEGREASER	COLD SOLVENT DEGREASER	4773A
POXNH3FLARE	AMMONIA FLARE	106.261/11/01/2003
PW310-50-1	EMERGENCY FIREWATER PUMP	4773A
ROCGEN	ROC GENERATOR	106.511/09/04/2000
SG13-20-1	RECTISOL DRAIN TANK	4773A
SG13-25-1	METHANOL STORAGE TANK	4773A
SG13-6-10	RECTISOL SURGE TANK	4773A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
SG20-2-2	ACID GAS FLARE	4773A
SG20-3-2	COLD FLARE	4773A
SG2022VENT	GRP 1 PROCESS VENT CONTROLLED BY ACID GAS FLARE	4773A
SG2032VENT	1 PROCESS VENT CONTROLLED BY COLD FLARE	4773A
SG21-1-1	HIGH PRESSURE FLARE	4773A
SG21-6-1	FLARE DRAIN TANK	4773A
SG2111VENT	FLARE HEADER FOR SG21-1-1	4773A
SG23-50-1	C.E. BOILER	4773A
SG23-51-1	SUPERHEATER	4773A
SG31PSA1	PSA UNIT	106.261/11/01/2003
SG41-31-1	SUPPLEMENTAL FEEDSTOCK TRUCK UNLOAD/LOAD STATION	106.473/09/04/2000
SG5-1-1	WASTEWATER HOLD TANK	106.472/09/04/2000
SG5-1-11	CARBON WATER SEPARATOR	106.472/09/04/2000
SG5-1-14	CARBON WATER TANK	4773A
SG5-1-17	GREY WATER TANK	4773A
SG5-7-1	WASTEWATER SURGE TANK	4773A
SG7-7-11	STRIPPER FEED TANK (FA-7)	4773A
SG810-21-1	NEUTRALIZATION TANK	4773A
SG810-22-1	EQUALIZATION TANK	4773A
SG810-27-1	DIVERSION TANK	106.472/09/04/2000
SG811-1-1	WASTE OIL TANK	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
SG811-3-1	WASTE OIL TANK	106.472/09/04/2000
SG930D	DIESEL TANK (FIXED)	4773A
SG930U	GASOLINE TANK (FIXED)	4773A
SGCT	COOLING TOWER SYSTEM	4773A
SGFUG	SYNGAS PLANT FUGITIVES	4773A
SGFUG1C3C	SYNGAS PROCESS & PROPYLENE REFRIGERATION FUGITIVES	4773A
WASTEWATER	PLANT WASTEWATEROPERATIONS	4773A
WW-103-34-10	GROUP 1 WASTE WATER STREAM	4773A, 40938
WW-103-34-8	GROUP 1 WASTE WATER STREAM	4773A, 40938
WW-103-34-9	GROUP 1 WASTE WATER STREAM	4773A, 40938
WW-103-35-11	GROUP 1 WASTE WATER STREAM	4773A, 40938
WW-105-20-1	STRIPPER COLUMN	4773A, 40938
WW-105-24-1	DESIGNATED GROUP 1 WW STREAM	4773A, 40938
WW-12-1-4	DESIGNATED GROUP 1 WW STREAM	4773A, 40938
WW-20-11-1.1	DESIGNATED GROUP 1 WW STREAM	4773A, 40938
WW-20-2-4	DESIGNATED GROUP 1 WW STREAM	4773A, 40938
WW-30-1-1	DESIGNATED GROUP 1 WW STREAM	4773A, 40938
WW-31-4-1	DESIGNATED GROUP 1 WW STREAM	4773A, 40938
WW-38-3-5A	DESIGNATED GROUP 1 WW STREAM	4773A, 40938
WW-38-3-5B	DESIGNATED GROUP 1 WW STREAM	4773A, 40938
WW-5-8-1	AUX FLARE KNOCK OUT TANK	4773A

	Appendix A	
Acronym I ist		76

Acronym List

The following abbreviations or acronyms may be used in this permit:

	actual aubia fact nor minuta
	actual cubic feet per minute
	alternate means of control
	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
	continuous emissions monitoring system
	continuous opacity monitoring system
CVS	closed vent system
D/FW	
	emission point
	U.S. Environmental Protection Agency
	emission unit
EU	emission unit
	Federal Clean Air Act Amendments
	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
	hydrogen sulfide
	identification number
	pound(s) per hour
MACT	
MMBtu/hr	Million British thermal units per hour
	Million British thermal units per hour nonattainment
NA	nonattainment
NA N/A	nonattainment not applicable
NA N/A NADB	nonattainment
NA	nonattainment
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60)
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60)
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate
NA	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate true vapor pressure
NA N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PM ppmv PRO PSD psia SIP SO2 TCEQ TSP TVP U.S.C.	nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate